

Få mere information om Microsoft RoundTable

For yderligere information om Microsoft RoundTable, Microsoft Office Communications Server 2007 og Office Live Meeting 2007, henvises til: www.microsoft.dk/uc.

Technical Specifications

Base

- Size (L x W x H): 350 x 350 x 360 mm
- Weight: 3.15 kg
- Power: 15 volts DC nominal, supplied by Power Data Box

Video

- Camera resolution: 3700 x 600 pixels
- Panoramic video resolution: 1056 x 144 pixels
- Active speaker video resolution
 - CIF: 352 x 288 pixels
 - VGA: 640 x 480 pixels
- Frame rate for panoramic and active speaker video:
 - 15 frames per second with 60 Hz AC power
 - 12.5 frames per second with 50 Hz AC power

Display

- High-resolution backlit graphical LCD
- Device status icons

Caller ID

- Bellcore Type 1 (requires telephone company subscription for activation)

Touch Screen

- 12-key telephone keypad
- Information navigation keys
- Delete key

Hard Keys

- On-hook/off-hook, flash, mute, volume up, volume down, information keys

Console Loudspeaker

- Frequency response: 300 Hz - 3.4 kHz in PBX/PSTN mode, 150 Hz - 7.5 kHz when used with Office Communications Server 2007 or Office Live Meeting 2007
- Volume: Adjustable to 89 dBA SPL (peak) volume at 0.5 meters

Console Microphones

- 6 directional microphones, 150 Hz - 3.4 kHz

Console Interface

- System cable: Proprietary interface to Power Data Box
- USB 2.0 device cable (480 Mbps link to PC)
- 2 USB host ports
- 2 satellite microphone connections

Power Data Box

- Size: 200 x 120 x 65 mm
- Weight: 0.55kg
- Power: 100 - 240 volts AC, 50 - 60 Hz, includes country-specific AC cable

Interfaces

- System cable: proprietary interface to Base
- Telecom interface: RJ-11 PBX or PSTN
- Data: RJ-45 10/100 Ethernet for system management
- Software download mode: Download server or command line via USB
- Network requirements: Compatible with standard PBX and PSTN networks
- Speech mode: Bandwidth of 300 Hz - 3.4 kHz for send and receive in PBX/PSTN mode, 150 - 3.4 kHz for send and 150 - 7.5 kHz for receive when used with Office Communications Server 2007 or Office Live Meeting 2007

Satellite Microphones (included)

- 2 directional satellite microphones, 150 Hz - 3.4 kHz

External Dial Pad (included)

- USB Human Interface Device (HID)
- 12-key keypad
- On-hook/off-hook, flash, mute, volume up, volume down and delete keys
- 16-character backlit alphanumeric display

Regulatory Compliance

- Safety
 - UL 60950-1
 - CSA C22.2 60950-1
 - IEC 60950-1
 - AS/NZS 60950-1
- EMC
 - CISPR 22 Class A (FCC, ICES, AS/NZS)
 - VCCI Class A
 - EN 55022 Class A
 - EN 55024
- Telecom
 - FCC Part 68
 - IC CS-03
 - AS/ACIF S002 & S004
 - ES 203 021
 - Ordinance No.31
 - ITU-T P.300

Environmental Requirements

- Operating temperature: 0° - 40°C
- Relative humidity: 15% - 85% (non condensing)
- Storage temperature: -40° - 60°C

Recommended Room Conditions

- Room reverberation time: RT60 <0.600 seconds
- Ambient noise level: <50 dBA SPL
- Optimal lighting conditions: 300 lux, with a single lighting temperature (no mixed lighting)
- Maximum recommended table length: 5 m

Warranty

- 12 months

Microsoft RoundTable ships with:

- Base with integrated 360-degree camera
- Power Data Box
- Satellite Microphones (2)
- External Dial Pad
- User documentation
- Cables
 - 1 power cable
 - 1 telephone cord, 2 m
 - 1 Ethernet cable, 2 m
- Telephone line adapter and filter (certain SKUs)

Requirements

- **Your infrastructure must include Microsoft Office Communications Server 2007 or Office Live Meeting 2007**
- **Microsoft RoundTable requires a computer with the following:**
 - Microsoft Windows® XP, 32-bit with service pack 2 (SP2) or later, or Windows Vista, 32- or 64-bit
 - 2.0 GHz or faster processor
 - 2 GB of RAM or more
 - 1.5 GB of available hard disk space
 - Video card with 128 MB of RAM or more and support for full hardware acceleration
 - 1024 x 768 or higher resolution video card and monitor
 - Wired Ethernet connection